



LOADING ELEVATORS



LOADING ELEVATOR WITH CONFIT TANK (OPM 506)

LOADING ELEVATORS CAN BE IN DIFFERENT STRUCTURE AND SIZE ACCORDING TO IT'S APPLICATION PURPOSE. THIS ENABLES CARRY AND TRANSFER OF THE PRODUCTS.ACCORDING TO THE USAGE AREA, IT CAN BE MANUFACTURED FROM STAINLESS ALUMINIUM OR IRON MATERIAL AND PVC MODULAR OR CAOUTCHOUC BELT IS USED.THIS TYPE ELEVATORS ARE DESIGNED FOR FEEDING PRODUCTS, MOREOVER, IT IS MANUFACTURED FROM STAINLESS MATERIAL, QUALITY OF 304



LOADING ELEVATOR WITH BUCKET (OPM 501)

LOADING ELEVATORS CAN BE IN DIFFERENT STRUCTURE AND SIZE ACCORDING TO IT'S APPLICATION PURPOSE.THIS ENABLES CARRY AND TRANSFER OF THE PRODUCTS.ACCORDING TO USAGE AREA,IT CAN BE MANUFACTURED FROM STAINLESS ALUMINIUM OR IRON MATERIAL AND PVC MODULAR OR CAOUTCHOUC BELT IS USED.THIS TYPE OF ELEVATOR SELECTION BELT OR ANOTHER PRODUCTION LINES ARE DESIGNED FOR FEEDING PRODUCTS.PRODUCT COMES FROM CONFIT TANKS OR DURING THE GREEN OLIVE PROCESSING, PRODUCT, WHICH SHOULD BE PROCESSED WITH WATER, SEPERATED FROM THE WATER,EVEN SUPPLYING THE PRODUCT.IT IS MANUFACTURED FROM STAINLESS MATERIAL QUALITY OF 304



CAN LOADING ELEVATOR (OPM 507)

LOADING ELEVATORS CAN BE IN DIFFERENT STRUCTURE AND SIZE ACCORDING TO IT'S APPLICATION AREA. THIS ENABLES CARRY AND TRANSFER OF THE PRODUCTS. ACCORDING TO USAGE AREA; IT CAN BE MANUFACTURED FROM STAINLESS ALUMINUM OR IRON MATERIAL AND PVC MODULAR OR CAOUTCHOUC BELT IS USED. THIS TYPE OF ELEVATOR IS DESIGNED FOR THE PURPOSE OF; DURING THE SHIPPING PROCESS, IT PROVIDES PACKAGED PRODUCTS SHIPPING TO THE TRUCK OR LORRY. IT CAN BE MANUFACTURED IN DIFFERENT SIZE AND MEASUREMENT. IT IS MANUFACTURED FROM STAINLESS MATERIAL OF 304 QUALITY



GENERAL PURPOSE LOADING ELEVATOR (OPM 502)

LOADING ELEVATORS CAN BE IN DIFFERENT STRUCTURE AND SIZE ACCORDING TO IT'S APPLICATION PURPOSE. THIS ENABLES CARRY AND TRANSFER OF THE PRODUCTS. ACCORDING TO USAGE AREA; IT CAN BE MANUFACTURED FROM STAINLESS ALUMINIUM OR IRON MATERIAL AND PVC, MODULAR OR CAOUTCHOUC BELT IS USED. THIS TYPE OF SELECTION ELEVATOR BELT IS DESIGNED FOR DIFFERENT SIZE AND MEASURED PRODUCT FEEDING IN ELEVATOR SELECTION BELT – CALIBRATION MACHINE – OLIVE SCRATCHING – CRUSHING MACHINES AND OTHER PRODUCTION LINES BEGINNING. IT IS MANUFACTURED FROM 304 QUALITY STAINLESS MATERIALS.



www.OliveProcessingMachines.com



LOADING ELEVATOR WITH MODULAR BELT (OPM 508)

LOADING ELEVATORS CAN BE IN DIFFERENT STRUCTURE AND SIZE ACCORDING TO IT'S APPLICATION AREA. THIS ENABLES, CARRY AND TRANSFER OF THE PRODUCTS. ACCORDING TO USAGE AREA; IT CAN BE MANUFACTURED FROM STAINLESS ALUMINIUM OR IRON MATERIAL AND PVC MODULAR OR CAOUTCHOUC BELT IS USED. THIS TYPE OF ELEVATOR IS USED LIKE LOADING ELEVATOR WITH BUCKET, NAMELY, WHEN WATERY PROCESSING IS REQUIRED BUT APART FROM LOADING ELEVATOR WITH BUCKET, IT IS MORE FUNCTIONAL AND UNPROBLEMATIC. MOREOVER, IT ENABLES PRODUCT WASHING PROCESS WITH CLEAN WATER ONE MORE TIME DURING PRODUCT IS OUT FROM WATER IN DEPOT